

Suttner Höchstdruckverschraubungen ST-740 und Stecknippel ST-741

Handverschraubungen ST-740 und Stecknippel ST-741



HV M24 : AG.
Max. 700 bar / 150 °C



HV M24 : AG.
Max. 700 bar / 150 °C



AG : M24 AG.
Max. 700 bar / 150 °C



M24 AG : M24 AG.
Max. 700 bar / 150 °C

⊙
3/8"
1/2"
M24

R+M Nr.
200 740 501
200 740 503

R+M Nr.
200 740 601

R+M Nr.
200 741 501
200 741 503

R+M Nr.
200 741 600



HV M24 : IG.
Max. 700 bar / 150 °C



HV M24 : IG.
Max. 700 bar / 150 °C



IG : M24 AG.
Max. 700 bar / 150 °C

⊙
1/4"
3/8"

R+M Nr.
200 740 504
200 740 502

R+M Nr.
200 740 604
200 740 602

R+M Nr.
200 741 504
200 741 502

Dichtungen



O-Ring - ST-740

R+M Nr.
050 000 408



O-Ring - ST-741

R+M Nr.
050 001 000



Stützring - ST-740

R+M Nr.
050 000 407

Suttner Höchstdruckschnellkupplungen ST-45-600

Kupplungen und Stecknippel ST-45-600



Kupplung : AG. Edelstahl.
Max. 600 bar / 150 °C



Kupplung : AG. Edelstahl.
Max. 600 bar / 150 °C



Stecknippel : IG. Edelstahl.
Max. 600 bar / 150 °C

⊙	DN
1/4"	8

R+M Nr.	ⓘ
200 045 600	57 mm

R+M Nr.	ⓘ
200 045 605	57 mm

R+M Nr.	ⓘ
040 005 468	40 mm



O-Ring. 11x1,5

R+M Nr.
050 000 020



Stützring. 11x14x1

R+M Nr.
050 001 430



O-Ring. 10x2,5

R+M Nr.
050 000 160