

Drehverschraubungen ST-241

Drehverschraubungen mit Innenabdichtung



HV 1/2" : IG. Max. 300 bar / 150 °C




HV 1/2" : AG. Max. 300 bar / 150 °C


⊙
1/4"
3/8"
1/2"

R+M Nr.	ⓘ
200 241 500	52 mm
200 241 520	52 mm
200 241 540	53 mm

R+M Nr.	ⓘ
200 241 510	56 mm
200 241 530	56 mm
200 241 550	58 mm



IG : 1/2" AG. Max. 300 bar / 150 °C



AG : 1/2" AG. Max. 300 bar / 150 °C



O-Ring Gegennippel

⊙
1/4"
3/8"
1/2"


R+M Nr.	ⓘ
200 241 700	34 mm
200 241 720	34 mm
200 241 740	36 mm

R+M Nr.	ⓘ
200 241 710	38 mm
200 241 730	38 mm
200 241 750	40 mm

R+M Nr.	VPE
050 000 160	1
791 025 100	100

Mosmatic Drehverschraubungen (Swivel)

Handverschraubung : Außengewinde



HV M22 : AG. Max. 250 bar / 120 °C



HV M21 : AG. Max. 250 bar / 120 °C



O-Ring Swivel MSM


⊙
1/4"
3/8"
M18
M22

R+M Nr.	ⓘ
108 701 01	47 mm
108 701 03	48 mm
108 701 07	42 mm
108 701 09	46 mm


R+M Nr.	ⓘ
108 700 01	47 mm
108 700 03	48 mm
108 700 07	42 mm

R+M Nr.	VPE
790 35	1
790 351 00	100

Handverschraubung : Innengewinde



HV M22 : IG. Max. 250 bar / 120 °C



HV M21 : IG. Max. 250 bar / 120 °C

⊙
1/4"
3/8"

R+M Nr.	ⓘ
108 701 02	47 mm
108 701 04	48 mm

R+M Nr.	ⓘ
108 700 02	47 mm
108 700 04	48 mm